



Next Generation Gloves

# CUT PRO

## C-5133

### Product Description

15-Gauge Cut D UHMWPE Shell

with Micro Foam Nitrile Palm Coating,

Screen Touch, and Thumb Crotch Reinforcement

### Composition

|                  |                            |
|------------------|----------------------------|
| Gauge            | 15                         |
| Liner Colour     | Royal Blue                 |
| Liner Material   | Polyester/NXG UCT™/spandex |
| Coating Material | Nitrile                    |
| Coating Colour   | Black                      |
| Coating Texture  | Micro Foam                 |
| Coating Area     | Palm                       |

### Application

- Electrical installation
- Light metal stamping
- Automotive assembly
- Utility services

### Main features

- Achieves up to TDM Level D for superior hand protection.
- Offers exceptional dexterity and a precise fit for maximum comfort.
- Touchscreen function, use your devices effortlessly without removing the gloves.
- Engineered for durability to handle the toughest tasks with ease.
- Micro foam nitrile coating delivers exceptional grip and enhanced tactile sensitivity for precision handling

### Dimension

| Size Range                    | Size 6(XS) | Size 7(S) | Size 8(M) | Size 9(L) | Size 10(XL) | Size 11(2XL) | Size 12(3XL) |
|-------------------------------|------------|-----------|-----------|-----------|-------------|--------------|--------------|
| Total glove length(+/- 10 mm) | 220        | 230       | 240       | 250       | 260         | 270          | 280          |
| Wrist length (mm)             | 72         | 75        | 78        | 81        | 84          | 87           | 90           |
| Wrist width (mm)              | 72         | 75        | 78        | 81        | 84          | 87           | 90           |
| Palm width (mm)               | 80         | 84        | 88        | 93        | 96          | 101          | 105          |
| Over lock colour              | Black      | Purple    | Green     | Coffee    | Yellow      | Grey         | Blue         |



### Performance Standards

EN388:2016 4X42D

EN407:2020 X1XXXX

